

CODIGO DE VALORES DE CAPACITORES CERAMICOS/MYLAR

VALOR	TIPO	CODG.	VALOR	TIPO	CODG.
1.5pF	Ceramic		1,000pF / .001uF	Ceramic / Mylar	102
3.3pF	Ceramic		1,500pF / .0015uF	Ceramic / Mylar	152
10pF	Ceramic		2,000pF / .002uF	Ceramic / Mylar	202
15pF	Ceramic		2,200pF / .0022uF	Ceramic / Mylar	222
20pF	Ceramic		4,700pF / .0047uF	Ceramic / Mylar	472
30pF	Ceramic		5,000pF / .005uF	Ceramic / Mylar	502
33pF	Ceramic		5,600pF / .0056uF	Ceramic / Mylar	562
47pF	Ceramic		6,800pF / .0068uF	Ceramic / Mylar	682
56pF	Ceramic		.01	Ceramic / Mylar	103
68pF	Ceramic		.015	Mylar	
75pF	Ceramic		.02	Mylar	203
82pF	Ceramic		.022	Mylar	223
91pF	Ceramic		.033	Mylar	333
100pF	Ceramic	101	.047	Mylar	473
120pF	Ceramic	121	.05	Mylar	503
130pF	Ceramic	131	.056	Mylar	563
150pF	Ceramic	151	.068	Mylar	683
180pF	Ceramic	181	.1	Mylar	104
220pF	Ceramic	221	.2	Mylar	204
330pF	Ceramic	331	.22	Mylar	224
470pF	Ceramic	471	.33	Mylar	334
560pF	Ceramic	561	.47	Mylar	474
680pF	Ceramic	681	.56	Mylar	564
750pF	Ceramic	751	1	Mylar	105
820pF	Ceramic	821	2	Mylar	205